

End-of-Life and Discontinued Product Announcement



Select Raritan PX3 4000 Series Rack PDUs

December 8, 2025

Legrand® announces the End-of-Life (EOL) and discontinuation of select Raritan® part numbers, listed in Table 1 below. Our team of power experts is ready to help you find an alternative or comparable Raritan product that best fits your needs.

Announcement Milestones

December 8, 2025	End-of-Life Announcement (EOLA) is the public notification date that commences the announcement that a product has been discontinued.
June 15, 2026	End of Sale/Last Order Date (EOS) is the last date to buy a product, order a new service contract, or add a product to an existing support contract. Thereafter, products and services are removed from all price lists.
June 15, 2026	End of New Contract Renewal Date (ENC) is the last date to order a new or extend an existing service or warranty contract.
June 15, 2028	End of Service Life (EOSL) is considered the final end-of-life milestone. It's the last date to receive service for the affected product(s) under a service contract or by warranty terms and conditions.

Table 1: Part Number(s) Affected by This Announcement

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-4025-H4M11N1	Contact us for assistance.	
PX3-4025-H4M11N1K1	Contact us for assistance.	
PX3-4025-H4M11N1K2	Contact us for assistance.	
PX3-4071V-V2	Contact us for assistance.	
PX3-4071V-V2K1	Contact us for assistance.	
PX3-4071V-V2K2	Contact us for assistance.	
PX3-4071V-V2K6	Contact us for assistance.	
PX3-4071V-V2K7	Contact us for assistance.	
PX3-4104A1R-M5V2	Contact us for assistance.	

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-4145R	PX4-44A7CR-A0	PX4, 1PH, 100-120V, 20A (16A/PH rated); 10 outlets: 10 x 5-20R, Input: IEC 60320 C20 Inlet, no cord, 1.9kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4145R-K1	PX4-44A7CR-A0	PX4, 1PH, 100-120V, 20A (16A/PH rated); 10 outlets: 10 x 5-20R, Input: IEC 60320 C20 Inlet, no cord, 1.9kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4145R-K2	PX4-44A7CR-A0	PX4, 1PH, 100-120V, 20A (16A/PH rated); 10 outlets: 10 x 5-20R, Input: IEC 60320 C20 Inlet, no cord, 1.9kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4166R	PX4-4256CR-C8E8A0	PX4, 1PH, 100-240V, 20A (16A/PH rated); 12 outlets: 8x C13, 4 x HDOT Cx, Input: IEC 60320 C20 Inlet, no cord, 1.6-3.8kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4166R-K1	PX4-4256CR-C8E8A0	PX4, 1PH, 100-240V, 20A (16A/PH rated); 12 outlets: 8x C13, 4 x HDOT Cx, Input: IEC 60320 C20 Inlet, no cord, 1.6-3.8kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4166R-K2	PX4-4256CR-C8E8A0	PX4, 1PH, 100-240V, 20A (16A/PH rated); 12 outlets: 8x C13, 4 x HDOT Cx, Input: IEC 60320 C20 Inlet, no cord, 1.6-3.8kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4167R	Contact us for assistance.	
PX3-4167R-A4	Contact us for assistance.	
PX3-4170U	Contact us for assistance.	
PX3-4170U-K1	Contact us for assistance.	
PX3-4170U-K2	Contact us for assistance.	
PX3-4170U-K6	Contact us for assistance.	
PX3-4180I2R	PX4-4256CR-C8E8A0	PX4, 1PH, 100-240V, 20A (16A/PH rated); 12 outlets: 8x C13, 4 x HDOT Cx, Input: IEC 60320 C20 Inlet, no cord, 1.6-3.8kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-4180I2R-K1	PX4-4256CR-C8E8A0	PX4, 1PH, 100-240V, 20A (16A/PH rated); 12 outlets: 8x C13, 4 x HDOT Cx, Input: IEC 60320 C20 Inlet, no cord, 1.6-3.8kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4180I2R-K2	PX4-4256CR-C8E8A0	PX4, 1PH, 100-240V, 20A (16A/PH rated); 12 outlets: 8x C13, 4 x HDOT Cx, Input: IEC 60320 C20 Inlet, no cord, 1.6-3.8kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4190CXR-E2	Contact us for assistance.	
PX3-4190CXR-E2K201	Contact us for assistance.	
PX3-4201R	PX4-4289R-E8	PX4, 1PH, 208V, 30A (24A/PH rated) ; 12 outlets: 8x C13, 4 x HDOT Cx, plug: NEMA L6-30P, 5.0kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4201R-E2	Contact us for assistance.	
PX3-4201R-E2A2	Contact us for assistance.	
PX3-4201R-E2A4	Contact us for assistance.	
PX3-4201R-K1	PX4-4289R-E8	PX4, 1PH, 208V, 30A (24A/PH rated) ; 12 outlets: 8x C13, 4 x HDOT Cx, plug: NEMA L6-30P, 5.0kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4201R-K2	PX4-4289R-E8	PX4, 1PH, 208V, 30A (24A/PH rated) ; 12 outlets: 8x C13, 4 x HDOT Cx, plug: NEMA L6-30P, 5.0kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4204R	PX4-4289I2R-C8E8	PX4, 1PH, 200-240V, 30A (24A/PH rated) or 32A ; 12 outlets: 8x C13, 4 x HDOT Cx, plug: IEC 60309 30/32A 2P+E 6h, 4.8-7.7kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4205R	PX4-4289I2R-C8E8	PX4, 1PH, 200-240V, 30A (24A/PH rated) or 32A ; 12 outlets: 8x C13, 4 x HDOT Cx, plug: IEC 60309 30/32A 2P+E 6h, 4.8-7.7kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4205R-E2	Contact us for assistance.	
PX3-4205R-E2K1	Contact us for assistance.	
PX3-4205R-K1	PX4-4289I2R-C8E8	PX4, 1PH, 200-240V, 30A (24A/PH rated) or 32A ; 12 outlets: 8x C13, 4 x HDOT Cx, plug: IEC 60309 30/32A 2P+E 6h, 4.8-

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
		7.7kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4205R-K2	PX4-4289I2R-C8E8	PX4, 1PH, 200-240V, 30A (24A/PH rated) or 32A ; 12 outlets: 8x C13, 4 x HDOT Cx, plug: IEC 60309 30/32A 2P+E 6h, 4.8-7.7kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4205R-K201	PX4-4289I2R-C8E8	PX4, 1PH, 200-240V, 30A (24A/PH rated) or 32A ; 12 outlets: 8x C13, 4 x HDOT Cx, plug: IEC 60309 30/32A 2P+E 6h, 4.8-7.7kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4205R-K3	PX4-4289I2R-C8E8	PX4, 1PH, 200-240V, 30A (24A/PH rated) or 32A ; 12 outlets: 8x C13, 4 x HDOT Cx, plug: IEC 60309 30/32A 2P+E 6h, 4.8-7.7kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4219-N1	Contact us for assistance.	
PX3-4260R	PX4-4256CR-C8E8A0	PX4, 1PH, 100-240V, 20A (16A/PH rated); 12 outlets: 8x C13, 4 x HDOT Cx, Input: IEC 60320 C20 Inlet, no cord, 1.6-3.8kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4260R-K1	PX4-4256CR-C8E8A0	PX4, 1PH, 100-240V, 20A (16A/PH rated); 12 outlets: 8x C13, 4 x HDOT Cx, Input: IEC 60320 C20 Inlet, no cord, 1.6-3.8kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4260R-K2	PX4-4256CR-C8E8A0	PX4, 1PH, 100-240V, 20A (16A/PH rated); 12 outlets: 8x C13, 4 x HDOT Cx, Input: IEC 60320 C20 Inlet, no cord, 1.6-3.8kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4260R-K5	PX4-4256CR-C8E8A0	PX4, 1PH, 100-240V, 20A (16A/PH rated); 12 outlets: 8x C13, 4 x HDOT Cx, Input: IEC 60320 C20 Inlet, no cord, 1.6-3.8kVA; Outlet Metered, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4405V	PX4-4475C-A0	PX4, 1PH, 120V, 20A (derated to 16A), 24 Outlets: 24 x NEMA 5-20R, Input: IEC 60320 C20 Inlet, no cord, 0U, 1.9kVA, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-4433V-E2	PX4-43A8C-C8E7A0	PX4, 1PH, 100-240V, 16A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60320 C20 Inlet, no cord, 0U, 1.6-3.8kVA, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4433V-E2K1	PX4-43A8C-C8E7A0	PX4, 1PH, 100-240V, 16A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60320 C20 Inlet, no cord, 0U, 1.6-3.8kVA, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4433V-E2K2	PX4-43A8C-C8E7A0	PX4, 1PH, 100-240V, 16A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60320 C20 Inlet, no cord, 0U, 1.6-3.8kVA, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4464-E2	PX4-4884-E7	PX4, 1PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L6-30P, 0U, 5.0kVA, 2 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4464-E2K1	PX4-4884-E7	PX4, 1PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L6-30P, 0U, 5.0kVA, 2 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4464-E2K2	PX4-4884-E7	PX4, 1PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L6-30P, 0U, 5.0kVA, 2 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4464R-Q1	PX4-4495R-E8	PX4, 1PH, 208V, 30A (24A/PH rated) ; 24 outlets: 18x C13, 6 x HDOT Cx, plug: NEMA L6-30P, 5.0kVA; Outlet Metered, 2U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4466V	PX4-4161-E7	PX4, 1PH, 230V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4466V-K1	PX4-4161-E7K1	PX4, 1PH, 230V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port. Red chassis

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-4466V-K2	PX4-4161-E7K2	PX4, 1PH, 230V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port. Blue chassis
PX3-4473V	PX4-4475C-A0	PX4, 1PH, 120V, 20A (derated to 16A), 24 Outlets: 24 x NEMA 5-20R, Input: IEC 60320 C20 Inlet, no cord, 0U, 1.9kVA, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4473V-K1	PX4-4475C-A0	PX4, 1PH, 120V, 20A (derated to 16A), 24 Outlets: 24 x NEMA 5-20R, Input: IEC 60320 C20 Inlet, no cord, 0U, 1.9kVA, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4473V-K2	PX4-4475C-A0	PX4, 1PH, 120V, 20A (derated to 16A), 24 Outlets: 24 x NEMA 5-20R, Input: IEC 60320 C20 Inlet, no cord, 0U, 1.9kVA, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4475	PX4-4475C-A0	PX4, 1PH, 120V, 20A (derated to 16A), 24 Outlets: 24 x NEMA 5-20R, Input: IEC 60320 C20 Inlet, no cord, 0U, 1.9kVA, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4488V	PX4-43A8C-C8E7A0	PX4, 1PH, 100-240V, 16A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60320 C20 Inlet, no cord, 0U, 1.6-3.8kVA, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4488V-H4M5	Contact us for assistance.	
PX3-4488V-H4M5A6K2	Contact us for assistance.	
PX3-4488V-H4M5K1	Contact us for assistance.	
PX3-4488V-K1	PX4-43A8C-C8E7A0	PX4, 1PH, 100-240V, 16A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60320 C20 Inlet, no cord, 0U, 1.6-3.8kVA, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4488V-K2	PX4-43A8C-C8E7A0	PX4, 1PH, 100-240V, 16A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60320 C20 Inlet, no cord, 0U, 1.6-3.8kVA, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4493	PX4-4161-E7	PX4, 1PH, 230V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered, iX controller with 2 x

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
		10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4493-K1	PX4-4161-E7	PX4, 1PH, 230V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4493-K2	PX4-4161-E7	PX4, 1PH, 230V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4496	PX4-4884-E7	PX4, 1PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L6-30P, 0U, 5.0kVA, 2 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4497YV-E2	Contact us for assistance.	
PX3-4500V	PX4-4161-E7	PX4, 1PH, 230V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4500V-K1	PX4-4161-E7	PX4, 1PH, 230V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4500V-K7	PX4-4161-E7	PX4, 1PH, 230V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4525V-E2Q1	Contact us for assistance.	
PX3-4525V-E2Q1A1	Contact us for assistance.	
PX3-4525V-E2Q1K1	Contact us for assistance.	
PX3-4525V-E2Q1K2	Contact us for assistance.	
PX3-4528U-E2N2V2	Contact us for assistance.	
PX3-4529V-E2V2	Contact us for assistance.	
PX3-4530V-N1K1	Contact us for assistance.	

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-4530V-N1K2	Contact us for assistance.	
PX3-4535V-Q1	Contact us for assistance.	
PX3-4535V-Q1K2	Contact us for assistance.	
PX3-4545-N1V2	Contact us for assistance.	
PX3-4545-N1V2K701	Contact us for assistance.	
PX3-4551-N5V2	Contact us for assistance.	
PX3-4551-N5V2K701	Contact us for assistance.	
PX3-4551U-E2V2	Contact us for assistance.	
PX3-4551U-E2V2A1	Contact us for assistance.	
PX3-4551U-E2V2A2	Contact us for assistance.	
PX3-4551U-E2V2K1	Contact us for assistance.	
PX3-4551U-E2V2K2	Contact us for assistance.	
PX3-4551U-E2V2K3	Contact us for assistance.	
PX3-4551U-E2V2K6	Contact us for assistance.	
PX3-4607R	PX4-4630I2R-C8E8	PX4, 3PH, WYE, 400/415V AC, 30A (24A/PH rated) and 32A; 24 outlets: 18x C13, 6x CX, plug: IEC 60309 3P+N+E (Wye Rear feed), 22.1 or 17.3kVA; Outlet Metered, 2U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4607R-K1	PX4-4630I2R-C8E8	PX4, 3PH, WYE, 400/415V AC, 30A (24A/PH rated) and 32A; 24 outlets: 18x C13, 6x CX, plug: IEC 60309 3P+N+E (Wye Rear feed), 22.1 or 17.3kVA; Outlet Metered, 2U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4607R-K3	PX4-4630I2R-C8E8	PX4, 3PH, WYE, 400/415V AC, 30A (24A/PH rated) and 32A; 24 outlets: 18x C13, 6x CX, plug: IEC 60309 3P+N+E (Wye Rear feed), 22.1 or 17.3kVA; Outlet Metered, 2U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-4612-E2N1V2	Contact us for assistance.	
PX3-4612-E2N1V2K1	Contact us for assistance.	
PX3-4612-E2N1V2K2	Contact us for assistance.	
PX3-4612R-E2	Contact us for assistance.	
PX3-4612R-E2K1	Contact us for assistance.	
PX3-4612R-E2K2	Contact us for assistance.	
PX3-4612R-E2K3	Contact us for assistance.	

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-4648V-M18	Contact us for assistance.	
PX3-4648V-M18K1	Contact us for assistance.	
PX3-4648V-M18K2	Contact us for assistance.	
PX3-4648V-M18P1	Contact us for assistance.	
PX3-4660U-E2P1A2	Contact us for assistance.	
PX3-4660U-E2P1K1	Contact us for assistance.	
PX3-4660U-E2P1K2	Contact us for assistance.	
PX3-4660U-E2P1K6	Contact us for assistance.	
PX3-4664U-E2P1	Contact us for assistance.	
PX3-4666V-C5	Contact us for assistance.	
PX3-4666V-C5K1	Contact us for assistance.	
PX3-4666V-C5K2	Contact us for assistance.	
PX3-4668-E2V2	PX4-4699-E7V2	PX4, 3PH, 400V, 32A, 36 Outlets: 18 x Locking C13, 18 x Locking HDOT Cx, Input: IEC 60309 3P+N+E, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4668-E2V2A6	PX4-4699-E7V2	PX4, 3PH, 400V, 32A, 36 Outlets: 18 x Locking C13, 18 x Locking HDOT Cx, Input: IEC 60309 3P+N+E, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4668-E2V2K1	PX4-4699-E7V2	PX4, 3PH, 400V, 32A, 36 Outlets: 18 x Locking C13, 18 x Locking HDOT Cx, Input: IEC 60309 3P+N+E, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4668-E2V2K2	PX4-4699-E7V2	PX4, 3PH, 400V, 32A, 36 Outlets: 18 x Locking C13, 18 x Locking HDOT Cx, Input: IEC 60309 3P+N+E, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4705-E2	Contact us for assistance.	
PX3-4719U	Contact us for assistance.	
PX3-4719U-E2N2	Contact us for assistance.	
PX3-4719U-E2N2K1	Contact us for assistance.	
PX3-4719U-E2N2K2	Contact us for assistance.	

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-4719U-K1	Contact us for assistance.	
PX3-4719U-K2	Contact us for assistance.	
PX3-4724U-E2P1	Contact us for assistance.	
PX3-4725V	PX4-42A0-E7	PX4, 3PH, 208V, 30A (derated to 24A), 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: NEMA L21-30P, 0U, 8.6kVA, 3 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4725V-K1	PX4-42A0-E7	PX4, 3PH, 208V, 30A (derated to 24A), 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: NEMA L21-30P, 0U, 8.6kVA, 3 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4725V-K2	PX4-42A0-E7	PX4, 3PH, 208V, 30A (derated to 24A), 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: NEMA L21-30P, 0U, 8.6kVA, 3 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4726YV-E2N1	Contact us for assistance.	
PX3-4726YV-E2N1K2	Contact us for assistance.	
PX3-4726YV-E2N1K9	Contact us for assistance.	
PX3-4731YV-V2	Contact us for assistance.	
PX3-4731YV-V2K1	Contact us for assistance.	
PX3-4731YV-V2K2	Contact us for assistance.	
PX3-4744I2U-V2	Contact us for assistance.	
PX3-4744I2U-V2K2	Contact us for assistance.	
PX3-4744I2U-V2K3	Contact us for assistance.	
PX3-4744I2U-V2K4	Contact us for assistance.	
PX3-4744I2U-V2K6	Contact us for assistance.	
PX3-4749NV-V2	Contact us for assistance.	
PX3-4755-O1D1	Contact us for assistance.	
PX3-4755-O1D1A2	Contact us for assistance.	
PX3-4755V	Contact us for assistance.	
PX3-4755V-K1	Contact us for assistance.	
PX3-4755V-K2	Contact us for assistance.	
PX3-4755V-K6	Contact us for assistance.	

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-4761R	Contact us for assistance.	
PX3-4786Y-E2V2	Contact us for assistance.	
PX3-4842U-E2	Contact us for assistance.	
PX3-4842V-E2	PX4-4057-E7	PX4, 1PH, 230V, 32A, 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4842V-E2A8	PX4-4057-E7	PX4, 1PH, 230V, 32A, 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4842V-E2K1	PX4-4057-E7	PX4, 1PH, 230V, 32A, 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4842V-E2K2	PX4-4057-E7	PX4, 1PH, 230V, 32A, 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4842V-E2K3	PX4-4057-E7	PX4, 1PH, 230V, 32A, 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4870U-E2P1	Contact us for assistance.	
PX3-4870YU-E2P1	Contact us for assistance.	
PX3-4905U-V2	Contact us for assistance.	
PX3-4905U-V2K1	Contact us for assistance.	
PX3-4905U-V2K2	Contact us for assistance.	
PX3-4905V-E2N3V2	Contact us for assistance.	
PX3-4917-V2	PX4-4917-E7V2	PX4, 3PH, 400V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking HDOT Cx, Input: IEC 60309 3P+N+E, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4917-V2K1	PX4-4917-E7V2	PX4, 3PH, 400V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking HDOT Cx, Input: IEC 60309 3P+N+E, 0U, 22.1kVA, 6 x

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
		10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-4917-V2K2	PX4-4917-E7V2	PX4, 3PH, 400V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking HDOT Cx, Input: IEC 60309 3P+N+E, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-495AV-E2F10N1	Contact us for assistance.	
PX3-4966V-F5M11V2	Contact us for assistance.	
PX3-4966V-F5M11V2K1	Contact us for assistance.	

Your Next Steps

We recommend following these steps to ensure you do what is best for your operations.

- Contact us to walk you through the process: call **800-724-8090** or **732-764-8886** and select 1 for Sales.
- Download the [discontinued Raritan part numbers list](#) to determine if an affected product/model in its end-of-life is in active use in your operations.
- Review your existing service contract terms to understand the [remaining coverage](#).
- Search the [Raritan PDU Product Selector](#) to find an alternative or comparable Raritan product – filter the Metering & Switching field on “Outlet Metered”, or contact your Raritan [sales representative](#), as a direct replacement product is often available.
- Breathe easy knowing that you will have [expert support](#) to help you during your transition to an alternative or comparable Raritan product offering.
- Opt in to [Support Notifications](#) and keep on top of future Raritan rack power distribution and rack management end-of-life announcements, the availability of firmware updates, and other critical product-related support updates.
- To learn more about our End-of-Life Policies for Raritan power distribution and rack management products, please visit [Raritan.com/power-eol](https://www.raritan.com/power-eol).