

End-of-Life and Discontinued Product Announcement



Select Raritan PX3 5000 Series Rack PDUs

December 8, 2025

Legrand® announces the End-of-Life (EOL) and discontinuation of select Raritan® part numbers, listed in Table 1 below. Our team of power experts is ready to help you find an alternative or comparable Raritan product that best fits your needs.

Announcement Milestones

December 8, 2025	End-of-Life Announcement (EOLA) is the public notification date that commences the announcement that a product has been discontinued.
June 15, 2026	End of Sale/Last Order Date (EOS) is the last date to buy a product, order a new service contract, or add a product to an existing support contract. Thereafter, products and services are removed from all price lists.
June 15, 2026	End of New Contract Renewal Date (ENC) is the last date to order a new or extend an existing service or warranty contract.
June 15, 2028	End of Service Life (EOSL) is considered the final end-of-life milestone. It's the last date to receive service for the affected product(s) under a service contract or by warranty terms and conditions.

Table 1: Part Number(s) Affected by This Announcement

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-5012-V2	Contact us for assistance.	
PX3-5012-V2K1	Contact us for assistance.	
PX3-5016A3-V2	Contact us for assistance.	
PX3-5025-M11N1	Contact us for assistance.	
PX3-5073CV-F5M5	Contact us for assistance.	
PX3-5073CV-F5M5K001	Contact us for assistance.	
PX3-5085U-N2	Contact us for assistance.	
PX3-5086R-F8	Contact us for assistance.	
PX3-5086R-F8K1	Contact us for assistance.	

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-5086R-F8K2	Contact us for assistance.	
PX3-5097	Contact us for assistance.	
PX3-5097-K1	Contact us for assistance.	
PX3-5097-K2	Contact us for assistance.	
PX3-5097-K4	Contact us for assistance.	
PX3-5097-K5	Contact us for assistance.	
PX3-5097-K7	Contact us for assistance.	
PX3-5098YU-V2	Contact us for assistance.	
PX3-5098YU-V2K1	Contact us for assistance.	
PX3-5098YU-V2K2	Contact us for assistance.	
PX3-5098YV-V2	Contact us for assistance.	
PX3-5098YV-V2K1	Contact us for assistance.	
PX3-5098YV-V2K2	Contact us for assistance.	
PX3-512ACJ-F5M22P1Q1	Contact us for assistance.	
PX3-512ACJ-F5M22P1Q1A0	Contact us for assistance.	
PX3-512ACJ-F5M22P1Q1A0K101	Contact us for assistance.	
PX3-512ACJ-F5M22P1Q1A0K201	Contact us for assistance.	
PX3-512ACJ-F5M22P1Q1A12K201	Contact us for assistance.	
PX3-512ACJ-F5M22P1Q1K101	Contact us for assistance.	
PX3-512ACJ-F5M22P1Q1K201	Contact us for assistance.	
PX3-5160U	Contact us for assistance.	
PX3-5184R	PX4-5256CR-C8E8A0	PX4, 1PH, 100-240V, 20A (16A/PH rated); 12 outlets: 8x C13, 4 x HDOT Cx, Input: IEC 60320 C20 Inlet, no cord, 1.6-3.8kVA; Outlet Metered/Switched, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-5184R-A1	PX4-5256CR-C8E8A0	PX4, 1PH, 100-240V, 20A (16A/PH rated); 12 outlets: 8x C13, 4 x HDOT Cx, Input: IEC 60320 C20 Inlet, no cord, 1.6-3.8kVA; Outlet Metered/Switched, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-5184R-K1	PX4-5256CR-C8E8A0	PX4, 1PH, 100-240V, 20A (16A/PH rated); 12 outlets: 8x C13, 4 x HDOT Cx, Input: IEC 60320 C20 Inlet, no cord, 1.6-3.8kVA; Outlet Metered/Switched, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-5193NR	PX4-5256CR-C8E8A0	PX4, 1PH, 100-240V, 20A (16A/PH rated); 12 outlets: 8x C13, 4 x HDOT Cx, Input: IEC 60320 C20 Inlet, no cord, 1.6-3.8kVA; Outlet Metered/Switched, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-5200R-Q2	PX4-5289R-E8	PX4, 1PH, 208V, 30A (24A/PH rated) ; 12 outlets: 8x C13, 4 x HDOT Cx, plug: NEMA L6-30P, 5.0kVA; Outlet Metered/Switched, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-5229V-E2Q1V2	Contact us for assistance.	
PX3-5229V-E2Q1V2K7	Contact us for assistance.	
PX3-5229V-E2Q2V2	Contact us for assistance.	
PX3-5229V-E2Q2V2K7	Contact us for assistance.	
PX3-5238V-Q1V2	Contact us for assistance.	
PX3-5238V-Q1V2K1	Contact us for assistance.	
PX3-5238V-Q1V2K2	Contact us for assistance.	
PX3-5252-N1V2	PX4-532A-E7V2	PX4, 3PH, 208V, 60A (derated to 48A), 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: IEC 60309 3P+E 60A, 0U, 17.3kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5252-N1V2K1	PX4-532A-E7V2K1	PX4, 3PH, 208V, 60A (derated to 48A), 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: IEC 60309 3P+E 60A, 0U, 17.3kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port. Red chassis
PX3-5252-N1V2K2	PX4-532A-E7V2K2	PX4, 3PH, 208V, 60A (derated to 48A), 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: IEC 60309 3P+E 60A, 0U, 17.3kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port. Blue chassis
PX3-5260NR	PX4-5256CR-C8E8A0	PX4, 1PH, 100-240V, 20A (16A/PH rated); 12 outlets: 8x C13, 4 x HDOT Cx, Input: IEC 60320 C20 Inlet, no cord, 1.6-3.8kVA; Outlet Metered/Switched, 1U horizontal PDU, SecureLock

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
		ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-5260NR-A6K2	PX4-5256CR-C8E8A0	PX4, 1PH, 100-240V, 20A (16A/PH rated); 12 outlets: 8x C13, 4 x HDOT Cx, Input: IEC 60320 C20 Inlet, no cord, 1.6-3.8kVA; Outlet Metered/Switched, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-5260NR-A6K3	PX4-5256CR-C8E8A0	PX4, 1PH, 100-240V, 20A (16A/PH rated); 12 outlets: 8x C13, 4 x HDOT Cx, Input: IEC 60320 C20 Inlet, no cord, 1.6-3.8kVA; Outlet Metered/Switched, 1U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-5260NR-H4	Contact us for assistance.	
PX3-5260NR-H4A4	Contact us for assistance.	
PX3-5260NR-H4A4K1	Contact us for assistance.	
PX3-5260V-F8	Contact us for assistance.	
PX3-5264X2	Contact us for assistance.	
PX3-5264X2-K1	Contact us for assistance.	
PX3-5264X2-K3	Contact us for assistance.	
PX3-5264X2-K7	Contact us for assistance.	
PX3-5266CR-F5	Contact us for assistance.	
PX3-5266CR-F5A0	Contact us for assistance.	
PX3-5292R-M11	Contact us for assistance.	
PX3-5296A1R-E2	Contact us for assistance.	
PX3-5296A1R-E2K4	Contact us for assistance.	
PX3-5296A1R-E2K5	Contact us for assistance.	
PX3-5299N-F5N3Q3V2	Contact us for assistance.	
PX3-5383X2-A4C5	Contact us for assistance.	
PX3-5383X2-C5	Contact us for assistance.	
PX3-5407CV	PX4-5475C-A0	PX4, 1PH, 120V, 20A (derated to 16A), 24 Outlets: 24 x NEMA 5-20R, Input: IEC 60320 C20 Inlet, no cord, 0U, 1.9kVA, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5407CV-A0	PX4-5475C-A0	PX4, 1PH, 120V, 20A (derated to 16A), 24 Outlets: 24 x NEMA 5-20R, Input: IEC 60320 C20 Inlet, no cord, 0U, 1.9kVA, Outlet

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
		Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5419-E2N1M9Q1	Contact us for assistance.	
PX3-5419-E2N1M9Q1A16	Contact us for assistance.	
PX3-5438CR	PX4-54A0CR-C8E8A0	PX4, 1PH, 100-240V, 20A (16A/PH rated); 24 outlets: 18 x C13, 6 x HDOT Cx, Input: IEC 60320 C20 Inlet, no cord, 1.6-3.8kVA; Outlet Metered/Switched, 2U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-5438CR-A0	PX4-54A0CR-C8E8A0	PX4, 1PH, 100-240V, 20A (16A/PH rated); 24 outlets: 18 x C13, 6 x HDOT Cx, Input: IEC 60320 C20 Inlet, no cord, 1.6-3.8kVA; Outlet Metered/Switched, 2U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-5460V	PX4-5884-E7	PX4, 1PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L6-30P, 0U, 5.0kVA, 2 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5466NR	PX4-5161-E7M27	PX4, 1PH, 230V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port, RCM B
PX3-5469V-M5	PX4-5161-E7M27	PX4, 1PH, 230V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port, RCM B
PX3-5469V-M5K1	PX4-5161-E7M27	PX4, 1PH, 230V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port, RCM B
PX3-5469V-M5K2	PX4-5161-E7M27	PX4, 1PH, 230V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port, RCM B
PX3-5469V-M5K201	PX4-5161-E7M27	PX4, 1PH, 230V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered and Switched, iX controller

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
		with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port, RCM B
PX3-5469V-M5K5	PX4-5161-E7M27	PX4, 1PH, 230V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port, RCM B
PX3-5478	Contact us for assistance.	
PX3-5482	PX4-53A8C-C8E7A0	PX4, 1PH, 100-240V, 16A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60320 C20 Inlet, no cord, 0U, 1.6-3.8kVA, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5482-A4	PX4-53A8C-C8E7A0	PX4, 1PH, 100-240V, 16A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60320 C20 Inlet, no cord, 0U, 1.6-3.8kVA, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5482-K1	PX4-53A8C-C8E7A0	PX4, 1PH, 100-240V, 16A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60320 C20 Inlet, no cord, 0U, 1.6-3.8kVA, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5486NV	Contact us for assistance.	
PX3-5487CV-N2	Contact us for assistance.	
PX3-5487U	Contact us for assistance.	
PX3-5487U-K1	Contact us for assistance.	
PX3-5487U-K2	Contact us for assistance.	
PX3-5487U-K201	Contact us for assistance.	
PX3-5488U	Contact us for assistance.	
PX3-5488U-A1	Contact us for assistance.	
PX3-5492U	PX4-59A0U-E7	PX4, 1PH, 120V, 30A (rated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L5-30P, 0U, 2.9kVA, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5493XV	Contact us for assistance.	
PX3-5493XV-K2	Contact us for assistance.	
PX3-5493XV-K5	Contact us for assistance.	

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-5495U-E2	PX4-5884U-E7	PX4, 1PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L6-30P (Top-end feed), 0U, 5.0kVA, 2 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5495U-E2A1	PX4-5884U-E7	PX4, 1PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L6-30P (Top-end feed), 0U, 5.0kVA, 2 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5495U-E2K1	PX4-5884U-E7	PX4, 1PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L6-30P (Top-end feed), 0U, 5.0kVA, 2 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5495U-E2K2	PX4-5884U-E7	PX4, 1PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L6-30P (Top-end feed), 0U, 5.0kVA, 2 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5495U-E2K7	PX4-5884U-E7	PX4, 1PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L6-30P (Top-end feed), 0U, 5.0kVA, 2 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5496U	PX4-5884U-E7	PX4, 1PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L6-30P (Top-end feed), 0U, 5.0kVA, 2 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5497	PX4-5884-E7	PX4, 1PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L6-30P, 0U, 5.0kVA, 2 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5497JV-N2	Contact us for assistance.	
PX3-5497JV-N2A19	Contact us for assistance.	
PX3-5497JV-N2A2	Contact us for assistance.	
PX3-5497JV-N2K1	Contact us for assistance.	
PX3-5497JV-N2K6	Contact us for assistance.	

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-5497-K1	PX4-5884-E7	PX4, 1PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L6-30P, 0U, 5.0kVA, 2 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5497-K5	PX4-5884-E7	PX4, 1PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L6-30P, 0U, 5.0kVA, 2 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5500A1V	Contact us for assistance.	
PX3-5500A1V-A12	Contact us for assistance.	
PX3-5500A1V-A12K501	Contact us for assistance.	
PX3-5503U	PX4-5161U-E7	PX4, 1PH, 230V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5503U-K1	PX4-5161U-E7	PX4, 1PH, 230V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5503U-K2	PX4-5161U-E7	PX4, 1PH, 230V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 2P+ E 32A, 0U, 7.4kVA, 2 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5520R-E2	Contact us for assistance.	
PX3-5520R-E2K1	Contact us for assistance.	
PX3-5520R-E2K2	Contact us for assistance.	
PX3-5521V	PX4-5548-E7	PX4, 3PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L15-30P, 0U, 8.6kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5522	PX4-5548-E7	PX4, 3PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L15-30P, 0U, 8.6kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-5523V	PX4-5548-E7	PX4, 3PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L15-30P, 0U, 8.6kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5523XV	Contact us for assistance.	
PX3-5523XV-K1	Contact us for assistance.	
PX3-5523XV-K2	Contact us for assistance.	
PX3-5524V-C5	PX4-5546-E7	PX4, 3PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L21-30P, 0U, 8.6kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5524V-C5K1	PX4-5546-E7	PX4, 3PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L21-30P, 0U, 8.6kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5524V-C5K2	PX4-5546-E7	PX4, 3PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L21-30P, 0U, 8.6kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5528A1V-V2	Contact us for assistance.	
PX3-5528A1V-V2K1	Contact us for assistance.	
PX3-5528A1V-V2K2	Contact us for assistance.	
PX3-5529V-N2V2	Contact us for assistance.	
PX3-5529V-N2V2A9K501	Contact us for assistance.	
PX3-5529V-N2V2K1	Contact us for assistance.	
PX3-5529V-N2V2K2	Contact us for assistance.	
PX3-5529V-N2V2K5	Contact us for assistance.	
PX3-5529V-N2V2K7	Contact us for assistance.	
PX3-5529XV-E2V2	Contact us for assistance.	
PX3-5529XV-E2V2K1	Contact us for assistance.	
PX3-5530N-V2	PX4-5917N-E7V2	PX4, 3PH, 400V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking HDOT Cx, Input: 32A Cord, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
		10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5530N-V2K1	PX4-5917N-E7V2	PX4, 3PH, 400V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking HDOT Cx, Input: 32A Cord, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5542-N2	Contact us for assistance.	
PX3-5545V-V2	PX4-5551-E7V2	PX4, 3PH, Delta, 208V, 60A (derated to 48A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 3P+E 60A, 0U, 17.3kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5545V-V2A16	PX4-5551-E7V2	PX4, 3PH, Delta, 208V, 60A (derated to 48A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 3P+E 60A, 0U, 17.3kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5545V-V2K1	PX4-5551-E7V2	PX4, 3PH, Delta, 208V, 60A (derated to 48A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 3P+E 60A, 0U, 17.3kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5545V-V2K2	PX4-5551-E7V2	PX4, 3PH, Delta, 208V, 60A (derated to 48A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 3P+E 60A, 0U, 17.3kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5545V-V2K7	PX4-5551-E7V2	PX4, 3PH, Delta, 208V, 60A (derated to 48A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: IEC 60309 3P+E 60A, 0U, 17.3kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5547V-V2	PX4-5547-E7V2	PX4, 3PH, 208V, 50A (derated to 40A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: CS8365C 50A, 0U, 14.4kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5547V-V2K1	PX4-5547-E7V2	PX4, 3PH, 208V, 50A (derated to 40A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: CS8365C 50A, 0U, 14.4kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-5547V-V2K2	PX4-5547-E7V2	PX4, 3PH, 208V, 50A (derated to 40A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: CS8365C 50A, 0U, 14.4kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5551-N5V2	Contact us for assistance.	
PX3-5551-N5V2K1	Contact us for assistance.	
PX3-5551-N5V2K701	Contact us for assistance.	
PX3-5551-N5V2K9	Contact us for assistance.	
PX3-5551XV-V2	Contact us for assistance.	
PX3-5561	Contact us for assistance.	
PX3-5561-K1	Contact us for assistance.	
PX3-5561-K2	Contact us for assistance.	
PX3-5561-K3	Contact us for assistance.	
PX3-5561-K5	Contact us for assistance.	
PX3-5592	PX4-5538-E7	PX4, 3Ph, 400V, 16A, 24 Outlets: 12 x Locking C13, 12 x HDOT Locking Cx, Input: IEC 60309 3P+N+E, 0U, 11.1kVA, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5599JV	PX4-5548J-E7	PX4, 3PH, 200V, 30A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L15-30P, 0U, 10.4kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5599JV-K1	PX4-5548J-E7	PX4, 3PH, 200V, 30A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L15-30P, 0U, 10.4kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5599JV-K2	PX4-5548J-E7	PX4, 3PH, 200V, 30A, 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L15-30P, 0U, 10.4kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5599R	PX4-5525R-E8	PX4, 3PH, 208V AC, 30A (24A/PH rated) ; 24 outlets: 18x C13, 6x CX, plug: NEMA L15-30P (Delta Rear feed), 8.6kVA; Outlet Metered/Switched, 2U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-5599V	PX4-5548-E7	PX4, 3PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L15-30P, 0U, 8.6kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5599V-K1	PX4-5548-E7	PX4, 3PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L15-30P, 0U, 8.6kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5599V-K2	PX4-5548-E7	PX4, 3PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L15-30P, 0U, 8.6kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5610I2R	PX4-5630I2R-C8E8	PX4, 3PH, WYE, 400/415V AC, 30A (24A/PH rated) and 32A; 24 outlets: 18x C13, 6x CX, plug: IEC 60309 3P+N+E (Wye Rear feed), 22.1 or 17.3kVA; Outlet Metered/Switched, 2U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-5610I2R-K1	PX4-5630I2R-C8E8	PX4, 3PH, WYE, 400/415V AC, 30A (24A/PH rated) and 32A; 24 outlets: 18x C13, 6x CX, plug: IEC 60309 3P+N+E (Wye Rear feed), 22.1 or 17.3kVA; Outlet Metered/Switched, 2U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-5610I2R-K2	PX4-5630I2R-C8E8	PX4, 3PH, WYE, 400/415V AC, 30A (24A/PH rated) and 32A; 24 outlets: 18x C13, 6x CX, plug: IEC 60309 3P+N+E (Wye Rear feed), 22.1 or 17.3kVA; Outlet Metered/Switched, 2U horizontal PDU, SecureLock ready, High resolution LCD display, iX, USB-A, USB-B and sensor connections
PX3-5612R-E2	Contact us for assistance.	
PX3-5660-E2	PX4-541A-E7	PX4, 3PH, 208V, 30A (derated to 24A), 39 Outlets: 18 x Locking C13, 18 x Locking Cx, 3 x NEMA 5-20R, Input: NEMA L21-30P, 0U, 8.6kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5660-E2K1	PX4-541A-E7	PX4, 3PH, 208V, 30A (derated to 24A), 39 Outlets: 18 x Locking C13, 18 x Locking Cx, 3 x NEMA 5-20R, Input: NEMA L21-30P, 0U, 8.6kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5660V-C1	Contact us for assistance.	

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-5660V-C1K9	Contact us for assistance.	
PX3-5665S1V	Contact us for assistance.	
PX3-5667U-E2V2	Contact us for assistance.	
PX3-5667U-E2V2A1K1	Contact us for assistance.	
PX3-5667U-E2V2A1K2	Contact us for assistance.	
PX3-5667U-E2V2K1	Contact us for assistance.	
PX3-5668N-M1101V2	Contact us for assistance.	
PX3-5668N-M1101V2A10K1	Contact us for assistance.	
PX3-5668N-M1101V2A10K201	Contact us for assistance.	
PX3-5668N-M1101V2A4K1	Contact us for assistance.	
PX3-5668N-M1101V2A4K201	Contact us for assistance.	
PX3-5668N-M1101V2A8K1	Contact us for assistance.	
PX3-5668N-M1101V2A8K201	Contact us for assistance.	
PX3-5668N-M1101V2K1	Contact us for assistance.	
PX3-5668N-M1101V2K201	Contact us for assistance.	
PX3-5668NU-E2M5V2A4K1	Contact us for assistance.	
PX3-5668NU-E2M5V2A4K201	Contact us for assistance.	
PX3-5668NU-E2M5V2K1	Contact us for assistance.	
PX3-5668NU-E2M5V2K201	Contact us for assistance.	
PX3-5668NU-E2M5V2K9	Contact us for assistance.	
PX3-5702JV	PX4-534AJ-E7	PX4, 3PH, 200V, 30A, 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: NEMA L15-30P (PSE), 0U, 10.4kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5702JV-A5K1	PX4-534AJ-E7	PX4, 3PH, 200V, 30A, 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: NEMA L15-30P (PSE), 0U, 10.4kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-5702JV-A5K2	PX4-534AJ-E7	PX4, 3PH, 200V, 30A, 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: NEMA L15-30P (PSE), 0U, 10.4kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5702JV-K1	PX4-534AJ-E7	PX4, 3PH, 200V, 30A, 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: NEMA L15-30P (PSE), 0U, 10.4kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5702JV-K2	PX4-534AJ-E7	PX4, 3PH, 200V, 30A, 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: NEMA L15-30P (PSE), 0U, 10.4kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5703V-E2V2	PX4-5699-E7V2	PX4, 3PH, 400V, 32A, 36 Outlets: 18 x Locking C13, 18 x Locking HDOT Cx, Input: IEC 60309 3P+N+E, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5703V-E2V2A2	PX4-5699-E7V2	PX4, 3PH, 400V, 32A, 36 Outlets: 18 x Locking C13, 18 x Locking HDOT Cx, Input: IEC 60309 3P+N+E, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5703V-E2V2K1	PX4-5699-E7V2	PX4, 3PH, 400V, 32A, 36 Outlets: 18 x Locking C13, 18 x Locking HDOT Cx, Input: IEC 60309 3P+N+E, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5703V-E2V2K2	PX4-5699-E7V2	PX4, 3PH, 400V, 32A, 36 Outlets: 18 x Locking C13, 18 x Locking HDOT Cx, Input: IEC 60309 3P+N+E, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5705-E2M5	Contact us for assistance.	
PX3-5705-E2M5A9	Contact us for assistance.	
PX3-5705-E2M5K1	Contact us for assistance.	
PX3-5705-E2M5K201	Contact us for assistance.	
PX3-5705N-E2M5	Contact us for assistance.	
PX3-5705N-E2M5K1	Contact us for assistance.	

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-5705N-E2M5K201	Contact us for assistance.	
PX3-5719U	Contact us for assistance.	
PX3-5719U-A16K2	Contact us for assistance.	
PX3-5719U-A16K5	Contact us for assistance.	
PX3-5719U-A8	Contact us for assistance.	
PX3-5719U-K2	Contact us for assistance.	
PX3-5719V	Contact us for assistance.	
PX3-5719V-A1K201	Contact us for assistance.	
PX3-5719V-A1K7	Contact us for assistance.	
PX3-5719V-K1	Contact us for assistance.	
PX3-5719V-K2	Contact us for assistance.	
PX3-5719V-K201	Contact us for assistance.	
PX3-5719V-K7	Contact us for assistance.	
PX3-5720	PX4-534A-E7	PX4, 3PH, 208V, 30A (derated to 24A), 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: NEMA L15-30P, 0U, 8.6kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5722-A5K1	PX4-5699-E7V2	PX4, 3PH, 400V, 32A, 36 Outlets: 18 x Locking C13, 18 x Locking HDOT Cx, Input: IEC 60309 3P+N+E, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5722-A5K2	PX4-5699-E7V2	PX4, 3PH, 400V, 32A, 36 Outlets: 18 x Locking C13, 18 x Locking HDOT Cx, Input: IEC 60309 3P+N+E, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5722-A6	PX4-5699-E7V2	PX4, 3PH, 400V, 32A, 36 Outlets: 18 x Locking C13, 18 x Locking HDOT Cx, Input: IEC 60309 3P+N+E, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5722-A6K1	PX4-5699-E7V2	PX4, 3PH, 400V, 32A, 36 Outlets: 18 x Locking C13, 18 x Locking HDOT Cx, Input: IEC 60309 3P+N+E, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-5724	PX4-534A-E7	PX4, 3PH, 208V, 30A (derated to 24A), 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: NEMA L15-30P, 0U, 8.6kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5724-K1	PX4-534A-E7	PX4, 3PH, 208V, 30A (derated to 24A), 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: NEMA L15-30P, 0U, 8.6kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5724-K2	PX4-534A-E7	PX4, 3PH, 208V, 30A (derated to 24A), 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: NEMA L15-30P, 0U, 8.6kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5729A1R	Contact us for assistance.	
PX3-5730N-M18	PX4-5699N-E7M28V2	PX4, 3PH, 400V, 32A, 36 Outlets: 18 x Locking C13, 18 x Locking HDOT Cx, Input: 32A Cord, no plug, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port, RCM B
PX3-5730N-M18K1	PX4-5699N-E7M28V2	PX4, 3PH, 400V, 32A, 36 Outlets: 18 x Locking C13, 18 x Locking HDOT Cx, Input: 32A Cord, no plug, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port, RCM B
PX3-5730U-M18	Contact us for assistance.	
PX3-5730U-M18K1	Contact us for assistance.	
PX3-5730U-M18K101	Contact us for assistance.	
PX3-5730U-M18K201	Contact us for assistance.	
PX3-5732-M11	Contact us for assistance.	
PX3-5732-M11A6	Contact us for assistance.	
PX3-5732-M11K1	Contact us for assistance.	
PX3-5732-M11K2	Contact us for assistance.	
PX3-5732U-F5	Contact us for assistance.	
PX3-5732U-F5A4	Contact us for assistance.	
PX3-5737U	Contact us for assistance.	
PX3-5737U-K1	Contact us for assistance.	

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-5739V	Contact us for assistance.	
PX3-5742U-V2	Contact us for assistance.	
PX3-5742U-V2K1	Contact us for assistance.	
PX3-5742U-V2K2	Contact us for assistance.	
PX3-5742U-V2K3	Contact us for assistance.	
PX3-5753V	Contact us for assistance.	
PX3-5755-D1	Contact us for assistance.	
PX3-5765I3V-N1V2	Contact us for assistance.	
PX3-5776U-N2	Contact us for assistance.	
PX3-5779V-P1V2	Contact us for assistance.	
PX3-5779V-P1V2A16	Contact us for assistance.	
PX3-5779V-P1V2A16K2	Contact us for assistance.	
PX3-5779V-P1V2A16K5	Contact us for assistance.	
PX3-5779V-P1V2A5	Contact us for assistance.	
PX3-5779V-P1V2K1	Contact us for assistance.	
PX3-5779V-P1V2K2	Contact us for assistance.	
PX3-5779V-P1V2K5	Contact us for assistance.	
PX3-5779V-P1V2K502	Contact us for assistance.	
PX3-5779V-P1V2K7	Contact us for assistance.	
PX3-5779V-P1V2K902	Contact us for assistance.	
PX3-5791U-M18V2	Contact us for assistance.	
PX3-5791U-M18V2K1	Contact us for assistance.	
PX3-5791U-M18V2K2	Contact us for assistance.	
PX3-5791U-M18V2K201	Contact us for assistance.	
PX3-5807	Contact us for assistance.	
PX3-582AI2U-F5M2N1Q2V2	Contact us for assistance.	
PX3-5871I2U-F1N2	Contact us for assistance.	
PX3-5871I2U-F1N2A1	Contact us for assistance.	
PX3-5871I2U-F1N2A8	Contact us for assistance.	
PX3-5871I2U-F1N2K201	Contact us for assistance.	

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-5871I2U-F1N2K7	Contact us for assistance.	
PX3-5872N-M5V2	Contact us for assistance.	
PX3-5872N-M5V2A6	Contact us for assistance.	
PX3-5872N-M5V2A6K1	Contact us for assistance.	
PX3-5872N-M5V2A6K2	Contact us for assistance.	
PX3-5872N-M5V2A6K9	Contact us for assistance.	
PX3-5872N-M5V2K1	Contact us for assistance.	
PX3-5872N-M5V2K2	Contact us for assistance.	
PX3-5872N-M5V2K9	Contact us for assistance.	
PX3-5902	PX4-5546-E7	PX4, 3PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L21-30P, 0U, 8.6kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5902-A5	PX4-5546-E7	PX4, 3PH, 208V, 30A (derated to 24A), 24 Outlets: 12 x Locking C13, 12 x Locking Cx, Input: NEMA L21-30P, 0U, 8.6kVA, 3 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5903	PX4-531A-E7	PX4, 1PH, 208V, 30A (derated to 24A), 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: NEMA L6-30P, 0U, 5.0kVA, 2 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5905I3V-V2	PX4-532A13-E7V2	PX4, 3PH, 208V, 60A (derated to 48A), 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: IEC 60309 3P+N+ E 60A, 0U, 17.3kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5905I3V-V2A1	PX4-532A13-E7V2	PX4, 3PH, 208V, 60A (derated to 48A), 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: IEC 60309 3P+N+ E 60A, 0U, 17.3kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5905I3V-V2A1K1	PX4-532A13-E7V2	PX4, 3PH, 208V, 60A (derated to 48A), 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: IEC 60309 3P+N+ E 60A, 0U, 17.3kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
PX3-5905I3V-V2K1	PX4-532A13-E7V2	PX4, 3PH, 208V, 60A (derated to 48A), 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: IEC 60309 3P+N+ E 60A, 0U, 17.3kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5905I3V-V2K2	PX4-532A13-E7V2	PX4, 3PH, 208V, 60A (derated to 48A), 36 Outlets: 18 x Locking C13, 18 x Locking Cx, Input: IEC 60309 3P+N+ E 60A, 0U, 17.3kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5905U-E2V2A2	Contact us for assistance.	
PX3-5905YV-V2	Contact us for assistance.	
PX3-5911N-M1801V2	Contact us for assistance.	
PX3-5911N-M1801V2A10K1	Contact us for assistance.	
PX3-5911N-M1801V2A10K2	Contact us for assistance.	
PX3-5911N-M1801V2A10K201	Contact us for assistance.	
PX3-5911N-M1801V2A6	Contact us for assistance.	
PX3-5911N-M1801V2K1	Contact us for assistance.	
PX3-5911N-M1801V2K201	Contact us for assistance.	
PX3-5917V-M5V2K1	Contact us for assistance.	
PX3-5917V-M5V2K201	Contact us for assistance.	
PX3-5917V-M5V2K3	Contact us for assistance.	
PX3-5917V-M5V2K5	Contact us for assistance.	
PX3-5917V-M5V2K6	Contact us for assistance.	
PX3-5917V-V2A6	PX4-5917-E7V2	PX4, 3PH, 400V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking HDOT Cx, Input: IEC 60309 3P+N+E, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5917V-V2K1	PX4-5917-E7V2	PX4, 3PH, 400V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking HDOT Cx, Input: IEC 60309 3P+N+E, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5917V-V2K2	PX4-5917-E7V2K2	PX4, 3PH, 400V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking HDOT Cx, Input: IEC 60309 3P+N+E, 0U, 22.1kVA, 6 x

End-of-Life Part Number	Suggested Replacement	
	Part Number	Description
		10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port. Blue chassis
PX3-5917V-V2K3	PX4-5917-E7V2	PX4, 3PH, 400V, 32A, 24 Outlets: 12 x Locking C13, 12 x Locking HDOT Cx, Input: IEC 60309 3P+N+E, 0U, 22.1kVA, 6 x 10kAIC breakers, Outlet Metered and Switched, iX controller with 2 x 10/100/1000 ETH port, 2 x USB-A, 1 x USB-B, RJ-45 Sensor and PDU Link port
PX3-5918I2V-C8N6V2	Contact us for assistance.	
PX3-59A5I2U-F5M2N1Q2V2	Contact us for assistance.	

Your Next Steps

We recommend following these steps to ensure you do what is best for your operations.

- Contact us to walk you through the process: call **800-724-8090** or **732-764-8886** and select 1 for Sales.
- Download the [discontinued Raritan part numbers list](#) to determine if an affected product/model in its end-of-life is in active use in your operations.
- Review your existing service contract terms to understand the [remaining coverage](#).
- Search the [Raritan PDU Product Selector](#) to find an alternative or comparable Raritan product – filter the Metering & Switching field on “Outlet Metered and Switched”, or contact your Raritan [sales representative](#), as a direct replacement product is often available.
- Breathe easy knowing that you will have [expert support](#) to help you during your transition to an alternative or comparable Raritan product offering.
- Opt in to [Support Notifications](#) and keep on top of future Raritan rack power distribution and rack management end-of-life announcements, the availability of firmware updates, and other critical product-related support updates.
- To learn more about our End-of-Life Policies for Raritan power distribution and rack management products, please visit Raritan.com/powerool.